

IMPROVED COUPLING ELEMENT FOR INVERTED T BEAMS

The present invention relates to an improved coupling element for inverted T beams.

Structural elements for false ceilings are known consisting of beams of 5 inverted T cross-section provided at their ends with hooks, which are either formed directly on the central web of the T beam or are in the form of inserts which are constructed separately and applied to each beam section during its construction.

Said beams are also provided in their web with cut-outs in which to 10 engage the coupling element of a beam perpendicular to it, to form a lattice structure which is generally suspended from the ceiling, usually by steel cables or tie bars, to functionally support with its horizontal flanges those panels and staves or the like necessary to form the false ceiling.

A known type of beam comprises an element which is subjected to 15 pressing to form an elastic strip in which, by cutting and plastic deformation, at least one tooth is defined having its abutment surface facing the beam, to form an insertion connection with the cut-out provided in the web of the beam.

A drawback of this coupling element is a certain laboriousness both in constructing the strip and in disengaging the strip from the cut-out in which it 20 is engaged.

An object of the invention is to provide an improved coupling element which enables the appendix to be easily and quickly engaged with and disengaged from the cut-out.

This and further objects which will be apparent from the ensuing 25 description are attained according to the invention by an improved coupling element for inverted T beams as claimed in claim 1.

The present invention is described in detail hereinafter with reference to the accompanying drawings, in which:

Figure 1 is a side view of a beam provided with the coupling element of the invention;

5 Figure 2 is a plan view of a coupling element inserted into the central web;

Figure 3 is an enlarged view of the coupling appendix;

Figure 4 is a side view thereof;

Figure 5 is a side view of a beam with the appendix formed in one piece therewith; and

10 Figure 6 is a plan view thereof.

As can be seen from the figures, the improved coupling element 2 of the invention is applied to the ends of the central web 4 of a beam of inverted T cross-section, said element being formed separately and applied to each beam part during its construction.

15 The coupling element comprises a substantially rectangular first portion 8 applied by traditional riveting to the ends of the central web, the portion 8 extending into a second portion 10 of lesser height which is bent substantially to V-shape with a portion 12 coplanar with the first portion 8 and with a second portion 14 comprising a tooth 16 obtained by cutting and plastic deformation, the free end of the tooth substantially facing the end of the first portion 8.

20

25 The central web 4 comprises a substantially rectangular cut-out 17 with its minor side provided with a projection 20 and with its major side having a length substantially corresponding to that of the second portion 10 of the coupling element.

In this manner the projection 20 defines two apertures 18 each suitable for engagement by the opposing part of the coupling elements.

To assemble the lattice structure, the operator inserts the V-bent element 8 of the coupling element 2 into the aperture 18 of the central web 4, 5 so compressing together the two parts 12, 14 of the second portion 10 until the free end of the tooth 16 becomes positioned on the other side of the web, to hence retain it with the end of the first portion 8 (see Figure 2).

When it becomes necessary to mutually disengage the beams, the operator presses the free end 14 of the V portion 10 so as to disengage the 10 undercut formed by the tooth 16 from the edge of the aperture 18 and then axially withdraws the coupling element therefrom.

In the embodiment shown in Figures 5 and 6 the coupling element is obtained directly during the beam construction.

From the foregoing it is clear that the improved coupling element 15 according to the invention presents the advantage not only of constructional simplicity, but also of a greater ease of release by virtue of the better accessibility of the appendix part to be pressed, without having to perform unusual manoeuvres.

C L A I M S

1. An improved coupling element for inverted T beams characterised by comprising at their ends an appendix (2) formed from two portions (8, 10) of different height, the outer portion (10) having the lesser height and being bent 5 to V-shape with the free part (14) comprising a tooth (16), and in their central web (4) at least one aperture (18) having a height substantially corresponding to the height of the outer portion (10), for the insertion of said portion and its stable retention by the tooth and by the edge of the inner portion (8).
2. An element as claimed in claim 1, characterised in that the appendix is 10 secured to the ends of the beam by riveting.
3. An element as claimed in claim 1, characterised in that the appendix is formed in one piece with the beam.

1/2

FIG. 1





FIG. 2



2/2




FIG. 5

FIG. 6






FIG. 3

FIG. 4



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12339

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E04B9/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 E04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 093 221 A (PURDY BURL O) 11 June 1963 (1963-06-11) column 2, line 18 - line 68; figures 2-4 ---	1
X	US 3 584 904 A (LICKLITER ROBERT P ET AL) 15 June 1971 (1971-06-15) column 3, line 5 - line 38; figures 3,4 ---	1,3
X	US 4 648 230 A (MIEYAL DAVID F ET AL) 10 March 1987 (1987-03-10) figures 1-3,5,7-9 -----	1-3

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

19 April 2004

Date of mailing of the international search report

26/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Demeester, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/12339

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 3093221	A	11-06-1963	NONE			
US 3584904	A	15-06-1971	US	3675957 A		11-07-1972
US 4648230	A	10-03-1987	DE	3624618 A1		29-01-1987
			FR	2585392 A1		30-01-1987
			GB	2178087 A ,B		04-02-1987
			GB	2200153 A ,B		27-07-1988
			GB	2199602 A ,B		13-07-1988
			JP	2097711 C		02-10-1996
			JP	7116785 B		18-12-1995
			JP	62059748 A		16-03-1987
			SE	461744 B		19-03-1990
			SE	8603187 A		25-01-1987
			SE	500457 C2		27-06-1994
			SE	8902972 A		11-09-1989
			SE	469899 B		04-10-1993
			SE	8902973 A		12-03-1991